

GemOne®

GEM-OX-L

Technical specifications



Our telematic hardware stands up to industrial demands.

With our GEM-OX-L device, you choose quality, for every make or model. The Onyx hardware is robustly built, is IP67-certified and is therefore dust- and water-resistant.

Plug and play. It's that simple.

Onyx

Power

Working voltage: 6 - 30V DC with over voltage protection

Battery: 400 mAh Ni-MH internal backup battery

Physical specifications

Dimensions: 2.854 × 2.874 × 1.075 inch

Weight: 0.45 lb

Ingress protection: IP67

Operating temp.: -40°F to 185°F

Conformity &

Certifications: CE/RED, E-Mark,
EAC, RoHS, REACH

GSM (data)

Internal high gain antenna

2G Quad-band 850 / 900 / 1800 / 1900 MHz

SMS / TCP / UDP

Internal 128MB flash memory for data

Connectivity

Bluetooth 4.0 + LE

2 status LEDs

3 digital inputs

2 digital outputs

1 analog input

1-wire interface + power

GNSS (positioning):

Receiver: GPS, GLONASS, GALILEO,
BEIDOU, SBAS, QZSS, DGPS,
AGPS

Antenna: Internal high gain antenna

Accuracy: < 9.84 ft

Supported peripherals

Built-in accelerometer

Temperature and humidity sensors

Universal BLE sensor support

iButton reader

RFID reader

For all industrial mixed fleets, regardless of the make or model

Contact us on info@gemone.com for more
information or a demonstration of the full GemOne
Onyx solution.

