

GemOne®

GEM-OX-L

Technical specifications



Our telematic hardware stands up to industrial demands.

With our GEM-OX-L device, you choose quality, for every make or model. The Onyx hardware is robustly built, is IP67-certified and is therefore dust- and water-resistant.

Plug and play. It's that simple.

Onyx

Power

Working voltage: 6 - 30V DC with over voltage protection
Battery: 400 mAh Ni-MH internal backup battery

Physical specifications

Dimensions: 72.5 × 73 × 27.3 mm
Weight: 205g
Ingress protection: IP67
Operating temp.: -40°C to +85 °C
Conformity & Certifications: CE/RED, E-Mark, EAC, RoHS, REACH

GSM (data)

Internal high gain antenna
2G Quad-band 850 / 900 / 1800 / 1900 MHz
SMS / TCP / UDP
Internal 128MB flash memory for data

Connectivity

Bluetooth 4.0 + LE
2 status LEDs
3 digital inputs
2 digital outputs
1 analog input
1-wire interface + power

GNSS (positioning):

Receiver: GPS, GLONASS, GALILEO, BEIDOU, SBAS, QZSS, DGPS, AGPS
Antenna: Internal high gain antenna
Accuracy: < 3 meters

Supported peripherals

Built-in accelerometer
iButton reader
RFID reader

For all industrial mixed fleets, regardless of the make or model

Contact us on info@gemone.com for more information or a demonstration of the full GemOne Onyx solution.

